

SPEED DOME CAMERA

KD-GD30\18
KD-GD30\22
KD-GD30\18DN



SPECIFICATION

IN DOOR	KD-GD30\18	KD-GD30\18DN	KD-GD30\22
OUT DOOR	KD-GW3\18	KD-GW3\18DN	KD-GW3\22
Image Sensor	SONY 1/4" CCD	SONY 1/4" Exview HAD CCD	1/4" Color SONY Hi-Res. Super HAD
Effective pixels	NTSC:768(H) x 494(V) PAL:752(H) x 582(V)		
Horizontal resolution	More than 470 TV lines		
Lens	18 x Zoom f 4.1 to 73.8 mm (F1.4 to F3.0)	22 x Zoom f3.9 to 85.8 mm (F1.6 to F3.7)	
Digital Zoom	12x(216x with optical)		10x (220x with optical)
Angle of View(H)	Approx.48°(wide end), approx.2.7°(tele end)		
Min. Object Distance	10 mm(wide end),800mm(tele end)		
Sync.System	Internal		
Minimum illumination	1.0 Lux	0.7 Lux ; 0.01Lux(IRCUTON)	1.0 Lux
S/N Ratio	More than 50dB		
White Balance	Auto,ATW,Indoor,Outdoor.One Push WB,Manual WB		
Focusing System	Auto(Sensitivity : H,L),On-Push AF,Manual,Infinity		
Panning range	360° endless		
Pan speed	0.5°-120°/sec		
Tilt range	0~90°		
Tilt speed	0.5~120°/secretary		
Communication	RS 485		
Controls	Pan/Tilt Lens 128 preset positions		
Auto Tracking	1 cruising tracks		
Power source mode	AC24V		

*Design and specifications are subject to change without prior notice



KND SECURITY

KND TECHNOLOGY CO., LTD.

<http://www.knd.com.tw>

E-mail:service@knd.com.tw

